

**HKE-HD**



Contact

Joe Caetano  
 02 4276 5400  
 joe.caetano@unipacsol.com.au



Combined strapping tool for steel strap

**Minimal effort for high-performance strap**

The HKE-HD is a special tool for using straps with a width of 19 mm and thickness from 0.6 to 0.8 mm. Processing such straps requires of course a little more effort than processing standard straps. The HKE-HD has a more voluminous body than its little brother, the HKE-L, to master the heavier loads with even more confidence. The longer levers make the job easier.

Apart from that, the typical HKE advantages are retained in the HD version: the TITAN-typical sealless joint with three notches is particularly suitable for flat packages.

Further advantages are the minimal risk of injury from this joint and the use of the HKE-HD in mobile applications. The HKE-HD is flexible enough for use in mobile applications.

**Technical Data**

Kind of drive (tensioning)	Manually
Tension force	up to approx. 6,000 N
Kind of drive (sealing)	Manually
Dimensions	570 x 130 x 190 (L x W x H)
Weight	4.2kg

**Strap/Joint**

Type of strap	Steel strap
---------------	-------------

Strap	up to approx. 1.100 N/mm <sup>2</sup> tensile strength
Strap width	19mm
Strap thickness	0.60 - 0.80mm
Kind of seal	Sealless-joint
Sealing strength (depending on strap quality, strap dimensions)	upto approx. 75% of the strap breaking load

**Minimum bearing area**

Flat package	150mm
--------------	-------

**Application**

Strapping of flat packages (e.g. palletized goods) for mobile use.